

	Revision Date 08/21/2017	Version 2.1
SiSECTION 1.Identification		
Product identifier		
Product number	113350	
Product name	2-Propanol for preparative chromatography Prepsolv®	
Synonyms	IPA, iPrOH	
CAS-No.	67-63-0	
Relevant identified uses of t	he substance or mixture and uses advised against	
Identified uses	Reagent for analysis, Solvent, Analytical and preparative chromatography	
Details of the supplier of the	safety data sheet	
Company	EMD Millipore Corporation 290 Concord Road, Billerica, MA 01821 United States of America General Inquiries: +1-978-715-4321 Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.	,
Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week	

SECTION 2. Hazards identification

GHS Classification

Flammable liquid, Category 2, H225 Eye irritation, Category 2A, H319 Specific target organ systemic toxicity - single exposure, Category 3, Central nervous system, H336 For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms



Signal Word Danger

Hazard Statements H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.

Product number	113350	Version 2
Product name	2-Propanol for preparative chromatography Prepsolv®	

H336 May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

-	-	
Formula	CH₃CH(OH)CH₃	C₃H₃O (Hill)
Synonyms	IPA, iPrOH	
Molar mass	60.1 g/mol	

Hazardous ingredients

Chemical name (Concentration) CAS-No. 2-Propanol (>= 90 % - <= 100 %) 67-63-0 Exact percentages are being withheld as a trade secret.

SECTION 4. First aid measures

Description of first-aid measures

Inhalation After inhalation: fresh air. Call in physician. 2.1

Product number	113350	Version 2.1
Product name	2-Propanol for preparative chromatography Prepsolv®	

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Ingestion

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

irritant effects, Headache, somnolence, respiratory paralysis, Drowsiness, Dizziness, inebriation, narcosis, Unconsciousness, Coma Drying-out effect resulting in rough and chapped skin.

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Foam, Carbon dioxide (CO2), Dry powder, Water

Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapors possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

Advice for firefighters

Special protective equipment for fire-fighters In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Product number	113350	Version 2.1
Product name	2-Propanol for preparative chromatography Prepsolv®	

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

Observe label precautions.

Advice on protection against fire and explosion Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Protected from light.

Store at $+5^{\circ}$ C to $+30^{\circ}$ C ($+41^{\circ}$ F to $+86^{\circ}$ F).

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

Ingredients			
Basis	Value	Threshold limits	Remarks
2-Propanol 67-0	63-0		
ACGIH	Time Weighted Average (TWA):	200 ppm	
	Short Term Exposure Limit (STEL):	400 ppm	
NIOSH/GUIDE	Recommended	400 ppm	
	exposure limit (REL):	980 mg/m³	
	Short Term Exposure	500 ppm	
	Limit (STEL):	1,225 mg/m ³	
OSHA_TRANS	PEL:	400 ppm	
		980 mg/m³	
Z1A	Short Term Exposure	500 ppm	
	Limit (STEL):	1,225 mg/m³	
	Time Weighted Average	400 ppm	
	(TWA):	980 mg/m³	

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Product number	113350	Version 2.7
Product name	2-Propanol for preparative chromatography Prepsolv®	

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

Eye/face protection Safety glasses

Hand protection

full contact:

	Glove material:	Nitrile rubber
	Glove thickness:	0.40 mm
	Break through time:	> 480 min
splash contact:		
	Glove material:	polychloroprene
	Glove thickness:	0.65 mm
	Break through time:	> 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 730 Camatril® -Velours (full contact), KCL 720 Camapren® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapors/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapors of organic compounds The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer. These measures have to be properly documented.

SECTION 9. Physical and chemical properties		
F	Physical state	liquid
C	Color	colorless
C	Ddor	alcohol-like
C	Ddor Threshold	1.0 - 196.1 ppm
p	рН	at 68 °F (20 °C) neutral

Product number Product name	113350 2-Propanol for preparative chromatography Prepsolv®	Version 2.1
Melting point	-129.1 °F (-89.5 °C)	
Boiling point/boiling range	180.3 °F (82.4 °C) at 1,013 hPa	
Flash point	54 °F (12 °C) Method: c.c.	
Evaporation rate	No information available.	
Flammability (solid, gas)	No information available.	
Lower explosion limit	2 %(V)	
Upper explosion limit	13.4 %(V)	
Vapor pressure	43 hPa at 68 °F (20 °C)	
Relative vapor density	2.07	
Density	0.786 g/cm3 at 68 °F (20 °C)	
Relative density	No information available.	
Water solubility	at 68 °F (20 °C) soluble	
Partition coefficient: n- octanol/water	log Pow: 0.05 OECD Test Guideline 107 Bioaccumulation is not expected.	
Autoignition temperature	No information available.	
Decomposition temperature	Distillable in an undecomposed state at normal pressure.	
Viscosity, dynamic	2.2 mPa.s at 68 °F (20 °C)	
Explosive properties	Not classified as explosive.	
Oxidizing properties	none	
Ignition temperature	797 °F (425 °C) Method: DIN 51794	
Minimum ignition energy	0.65 mJ	
Conductivity	< 0.1 µS/cm	

Product number113350Product name2-Propanol for preparative chromatography Prepsolv®

SECTION 10. Stability and reactivity

Reactivity

Formation of peroxides possible. Vapors may form explosive mixture with air.

Chemical stability

Sensitivity to light Sensitive to air.

Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapors with:

Alkali metals, Alkaline earth metals, chromium(VI) oxide

Exothermic reaction with:

Oxidizing agents, Nitric acid, Aldehydes, Amines, fuming sulfuric acid, Iron, Aluminum, Chlorine, PHOSPHORUS TRICHLORIDE, Strong acids

Risk of explosion with:

chlorates, Phosgene, organic nitro compounds, hydrogen peroxide, nitrogen oxides, perchlorates

Conditions to avoid

Warming.

Incompatible materials

rubber, various plastics, oils

Hazardous decomposition products

Peroxides

SECTION 11. Toxicological information Information on toxicological effects

Likely route of exposure Inhalation, Eye contact, Skin contact

Target Organs Eyes Skin Respiratory system *Acute oral toxicity* LDLO human: 3,570 mg/kg (RTECS)

LD50 Rat: 5,045 mg/kg (RTECS)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Acute inhalation toxicity LC50 Rat: 37.5 mg/l; 4 h ; vapor OECD Test Guideline 403

Product number113350Product name2-Propanol for preparative chromatography Prepsolv®

Symptoms: Possible damages:, mucosal irritations

Acute dermal toxicity LD50 Rabbit: 12,800 mg/kg (RTECS)

Skin irritation Rabbit Result: No skin irritation OECD Test Guideline 404

Drying-out effect resulting in rough and chapped skin.

Eye irritation Rabbit Result: Eye irritation OECD Test Guideline 405

Causes serious eye irritation.

Sensitization Buehler Test Guinea pig Result: negative Method: OECD Test Guideline 406

Repeated dose toxicity Subchronic toxicity

Genotoxicity in vivo In vivo micronucleus test Mouse Result: negative Method: OECD Test Guideline 474

Genotoxicity in vitro Ames test Salmonella typhimurium Result: negative Method: OECD Test Guideline 471

In vitro mammalian cell gene mutation test Result: negative Method: OECD Test Guideline 476

Carcinogenicity Method: OECD Test Guideline 451 Did not show carcinogenic effects in animal experiments.

Reproductive toxicity No impairment of reproductive performance in animal experiments. (IUCLID)

Teratogenicity Did not show teratogenic effects in animal experiments. (IUCLID)

Specific target organ systemic toxicity - single exposure

Product number	113350	Version 2.1
Product name	2-Propanol for preparative chromatography Prepsolv®	

May cause drowsiness or dizziness. Target Organs: Central nervous system

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

0	
IARC	No ingredient of this product present at levels greater than or
	equal to 0.1% is identified as probable, possible or confirmed
	human carcinogen by IARC.
OSHA	No ingredient of this product present at levels greater than or
	equal to 0.1% is identified as a carcinogen or potential
	carcinogen by OSHA.
NTP	No ingredient of this product present at levels greater than or
	equal to 0.1% is identified as a known or anticipated carcinogen
	by NTP.
ACGIH	No ingredient of this product present at levels greater than or
	equal to 0.1% is identified as a carcinogen or potential
	carcinogen by ACGIH.

Further information

After absorption: Headache, Dizziness, inebriation, Unconsciousness, narcosis Systemic effects: After uptake of large quantities: respiratory paralysis, Coma Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

Toxicity to fish flow-through test LC50 Pimephales promelas (fathead minnow): 9,640 mg/l; 96 h US-EPA Toxicity to daphnia and other aquatic invertebrates EC5 E.sulcatum: 4,930 mg/l; 72 h (maximum permissible toxic concentration) (Lit.) EC50 Daphnia magna (Water flea): 13,299 mg/l; 48 h (IUCLID) Toxicity to algae IC50 Desmodesmus subspicatus (green algae): > 1,000 mg/l; 72 h (IUCLID) Toxicity to bacteria EC5 Pseudomonas putida: 1,050 mg/l; 16 h (Lit.)

Persistence and degradability

Product number	113350
Product name	2-Propanol for preparative chromatography Prepsolv®

Biodegradability 95 %; 21 d; aerobic OECD Test Guideline 301E Readily biodegradable.

Theoretical oxygen demand (ThOD) 2,400 mg/g (Lit.) *Ratio BOD/ThBOD* BOD5 49 % (IUCLID) *Ratio COD/ThBOD*

96 % (Lit.)

Bioaccumulative potential

Partition coefficient: n-octanol/water log Pow: 0.05 OECD Test Guideline 107 Bioaccumulation is not expected.

Mobility in soil

No information available.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)	
UN number	UN 1219
Proper shipping name	ISOPROPANOL
Class	3
Packing group	II
Environmentally hazardous	
Air transport (IATA) UN number Proper shipping name Class Packing group Environmentally hazardous Special precautions for user	UN 1219 ISOPROPANOL 3 II no

Sea transport (IMDG)

Product number	113350	Version 2.1
Product name	2-Propanol for preparative chromatography Prepsolv®	

UN number	UN 1219
Proper shipping name	ISOPROPANOL
Class	3
Packing group	II
Environmentally hazardous	
Special precautions for user EmS	yes F-E S-D

SECTION 15. Regulatory information

United States of America

SARA 313

The following components are subject to reporting levels established by SARA Title III, Section 313: Ingredients

2-Propanol 67-63-0 100 %

SARA 302

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311,

Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311,

Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

DEA List I

Not listed

DEA List II Not listed

US State Regulations

Massachusetts Right To Know

Ingredients 2-Propanol

Pennsylvania Right To Know

Ingredients 2-Propanol

New Jersey Right To Know

Ingredients 2-Propanol California Prop 65 Components

Product number	113350	Version 2.1
Product name	2-Propanol for preparative chromatography Prepsolv®	

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

TSCA:	All components of the product are listed in the TSCA-inventory.
DSL:	All components of this product are on the Canadian DSL

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Labeling Hazard pictograms

Signal Word Danger

Hazard Statements H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary Statements

Prevention P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P240 Ground/bond container and receiving equipment. Response P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Storage P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Product number113350VProduct name2-Propanol for preparative chromatography Prepsolv®V

Version 2.1

Revision Date08/21/2017

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.